


Non-rotation Rope or Hercules Rope

非自轉性鋼纜



WSH 35

鋼纜直徑 (mm)	拉斷負荷						(參考) 概算 單位質量 kg/m
	無鍍鋅 · 鍍鋅						
	1770 N/mm ² (180 kgf/mm ²)		1960 N/mm ² (200 kgf/mm ²)		2160 N/mm ² (220 kgf/mm ²)		
	kN	{ tf }	kN	{ tf }	kN	{ tf }	
8	44.0	{4.5}	49	{5.0}	52	{5.4}	0.292
10	68.8	{7.02}	77	{7.85}	82	{8.36}	0.457
11	83.2	{8.49}	93	{9.50}	100	{10.2}	0.553
12	99.0	{10.1}	111	{11.3}	119	{12.1}	0.658
13	116	{11.9}	131	{13.4}	140	{14.3}	0.772
14	135	{13.8}	152	{15.5}	162	{16.5}	0.896
15	155	{15.8}	174	{17.7}	186	{19.0}	1.03
16	176	{18.0}	197	{20.1}	211	{21.5}	1.17
18	222	{22.6}	250	{25.5}	268	{27.3}	1.48
20	275	{28.1}	308	{31.4}	328	{33.4}	1.83
22	333	{34.0}	373	{38.0}	397	{40.5}	2.21
24	396	{40.4}	444	{45.2}	472	{48.2}	2.63
26	465	{47.4}	521	{53.1}	554	{56.5}	3.09
28	539	{55.0}	604	{61.6}	643	{65.6}	3.58
30	619	{63.1}	693	{70.7}	738	{75.3}	4.11
32	705	{71.8}	788	{80.4}	840	{85.6}	4.68
34	795	{81.1}	890	{90.8}	948	{96.7}	5.28
36	892	{90.9}	998	{102}	1060	{108}	5.92
38	993	{101}	1110	{113}	1180	{120}	6.60
40	1100	{112}	1230	{125}	1310	{134}	7.31